




- Electronic battery charger and trickle charger, with TRONIC technology for 6/12V lead WET, GEL, AGM, MF, EFB type batteries.
- Automatic recognition of 6/12V battery voltage.
- LED signalling of the charge, charging ended.
- Protection against overloads, short circuit and polarity reversal.
- Dust, humidity and water resistant. IP54.

TECHNICAL DATA

CODE	807558	CHARGING VOLTAGE	6 / 12 V	MAX.RATED REFERENCE CAPAC.	20 Ah
SINGLEPHASE MAINS VOLTAGE	100 - 240 V	EFFICIENT CHARGING CURRENT	0,75 A	PROTECTION DEGREE	IP54
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	0,75 A	DIMENSIONS (LxWxH)	5 x 8 x 3 cm
CHARGING ABSORBED POWER	15 W	MIN.RATED REFERENCE CAPAC.	2 Ah	WEIGHT	0,22 kg

SUPPLIED ACCESSORIES

124763	CLAMPS CONNECTION CABLE
124901	EYELETS PATCH CORD

DESCRIPTION

Intelligent battery charger and maintainer with electronic control of the charging current, automatic interruption and restart (TRONIC) for charging 6/12V lead-acid batteries type WET, GEL, AGM, MF, EFB.

Features:

- Automatic detection of 6/12V battery voltage;
- LED signalling battery on charge, end of charge;
- Protection against overloads, short circuits and polarity reversal.

Complete with cable with clamps and cable with eyelets.

DOWNLOAD



CATALOG IMAGE



CERTIFICATE

USEFUL LINKS



VIDEO