IVR-B 20/8

Small, versatile IVR-B 20/8 build-in unit with stainless steel container and side channel blower. Suitable for vacuuming press remnants, shavings and coarse dust.

Made in Germany

Order no.	9.989-417.0

- Compact dimensions
- Freestanding stainless steel collection container

Technical data

EAN code		4054278695099
Number of current phases	**Ph**	3
Voltage	**V**	400
Frequency	**Hz**	50 – 60
Air flow	**l/s / m³/h**	39 / 140
Vacuum	**mbar / kPa**	90 / 9
Container capacity	**l**	20
Rated input power	**kW**	0.8
Vacuuming type		Electric
Connection nominal diameter		DN 50
Accessory nominal diameter		DN 50 / DN 40
Sound pressure level	**dB(A)**	70
Main filter dust class		M
Filter area for main filter	**m²**	0.7
Weight without accessories	**kg**	32
Weight incl. packaging	**kg**	32.6
Dimensions (L × W × H)	**mm**	610 × 450 × 480

Equipment

Container emptying: Set-down trolley

IVR-B 20/8, 9.989-417.0, 2026-10-02

Compact dimensions

- Easy storage and attachment between, on or under production machines.
- The compact size makes it suitable for a range of different applications.
- Powerful side channel blower facilitates diverse applications.

Freestanding stainless steel collection container

- The collection container can be lifted off the base plate of the machine.
- Safety clips on the lid enable safe transport.

Wear-resistant side channel blower

- Compact machine with 0.8 kW rated input power for vacuuming solids.
- For strong suction power and service life of at least 20,000 hours.
- Optimally suited for mobile use in multiple shift operation.

IVR-B 20/8, 9.989-417.0, 2026-10-02

ACCESSORIES FOR IVR-B 20/8
9.989-417.0

2

3

4


5

6

7

8–9

10–11

12–13

14

		Order no.	Description	
FILTERS				
Cartridge filter				
Cartridge filter PE M 0,7m² m. Bohrung	1	9.979-291.0		■
NOZZLES				
Standard nozzles				
Standard PVC nozzle DN40	2	9.989-674.0	Electroconductive standard PVC nozzle. DN 40.	☐
Standard nozzle silicone DN40	3	9.988-401.0	Stretchy standard nozzle made from silicone, inner cone DN 40.	☐
Standard nozzle cuttable rubber DN40	4	9.989-677.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 40.	☐
Standard aluminium nozzle DN40	5	9.980-748.0	Diagonal nozzle made from anodised aluminium, electroconductive, DN 40.	☐
Crevice nozzles				
Crevice nozzle PP 15 mm × 145 mm DN40	6	9.988-116.0	Electroconductive, flat multi-purpose crevice nozzle made from plastic, DN 42.	☐
Surface nozzles				
Silicone surface nozzle 120 mm DN40	7	9.988-118.0	Electroconductive rubber nozzle, angled, DN 40, suitable for use with foods.	☐
HOSES				
PVC				
Hose PVC DN40 3 m	8	9.989-647.0	PVC hose, DN 40. Temperature-resistant up to 85 °C and electrically conductive. Length: 3 m.	☐
Hose PVC DN40 5 m	9	9.989-614.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 5 m.	☐
EVA hoses				
Hose EVA NW40 3 m	10	9.988-088.0	Electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 3 m.	☐
Hose EVA NW40 5 m	11	9.988-089.0	Five-metre-long, electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 5 m.	☐
PU hoses				
Hose PU DN40 3 m	12	9.989-617.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN40 5 m	13	9.989-618.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
HANDLES				
Handle DN 40	14	9.977-679.0	45° curved and electroconductive handle made from stainless steel. Inner cone DN 40.	☐

■ Included in the scope of supply. ☐ Available accessories.

ACCESSORIES FOR IVR-B 20/8
9.989-417.0

		Order no.	Description	
ADAPTERS / REDUCERS / DISTRIBUTORS				
Reducers/expanders				
Reduction DN50 to DN40	15	9.981-231.0	Reducer from DN 50 to DN 40. Material: Steel. Electroconductive.	☐

☐ Available accessories.