



**WACKER
NEUSON**
all it takes!

DPU 3750Hets

5000610322

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Plates](#) >> [Reversible Vibratory Plates](#) >> **DPU 3750Hets**

DPU 3750Hets

Material number 5000610322

Reversible vibratory plate with diesel engine and electric starter.
The flexible all-rounder for soil, asphalt and pavement compaction.



Product details

Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Comes with

- Vibratory plate
- Operator's manual

Technical specifications

DPU 3750Hets

OPERATING FLUIDS	Metric
Tank capacity	5,00 l
Exciter oil volume	0,60 l
Hydraulic fluid type	Renolin MR 520
Hydraulic fluid volume	0,285 l
Exciter oil type	75W-90 API GL-4

ENGINE	Metric
Battery capacity (nom. value)	18 Ah
Inclined position max.	25,0 °
Air cleaner	Dry air filter
Power rating max.	5,4 kW
Engine operating mode	four-stroke
fuel type	Diesel EN 590
Cooling	air cooling
Exhaust-gas limit	EU Stage V
Oil specification	SAE 10W-40
Starter battery Voltage	12 V
Fuel consumption	0,60 l/Std
Engine speed (Power max.)	3.600 1/min
Starter type	Recoil starter
Oil filling min.	0,60 l
Engine type	Diesel engine
Cylinder	1
Standard (Power max.)	ISO 3046 IFN
Engine Manufacturer	Hatz
Cylinder capacity	347 cm3
Nominal Engine speed	null, 2.800 1/min

Oil filling max.	1,10 l
Effective power	null, 4,2 kW
Oil volume incl. filter change	1,10 l

MECHANICAL - OUTPUT DETAILS	Metric
Vibrations	5.400 1/min
Forward running	24,00 m/min
Transmission	FKK
Gradeability	46,6 %
Centrifugal force	37,000 kN
Vibrations (Hz)	90,0 Hz
Area capacity	720 m2/h

ENVIRONMENT DATA	Metric
Operating temperature range	-15 - 45 °C
Sound level LpA (Standard)	EN 500-4
Sound power LWA, guaranteed	108,0 dB(A)
Storage temperature range	-15 - 45 °C
HAV summation (average value)	2,5 m/s2
Uncertainty in measurement HAV	0,5 m/s2
HAV summation (Standard)	EN 500-4
Sound level LpA	86,0 dB(A)
Sound power LWA (Standard)	EN 500-4, 2000/14/EG
Sound power LWA, measured	107,0 dB(A)

MECHANICAL DETAILS	Metric
Lenght Drawbar in op. pos.	1.295 mm
Operating weight	265,0 kg
Height	1.101 mm
Underclearance	777 - 887 mm
Width	500 mm

Custom Attributes

Metric

Model serie

DPU

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE