



**WACKER
NEUSON**
all it takes!

AR26/6/042 cs

5100003940

[Home](#) >> [Catalog](#) >> [Products](#) >> [Concrete Technology](#) >> [External Vibrators](#) >> [Compaction of In-Situ Concrete](#) >> **AR26/6/042 cs**



AR26/6/042 cs

Material number 5100003940

External vibrator for exposed concrete with On/Off switch in power cable. Series 2, type of fastening 6, 6000 rpm, protective low voltage.

Product details

Highlights

- Small, compact and light
- Asynchronous motor with stable speed
- Sturdy design

Comes with

- External vibrator, including power cable
- Operator's manual

Technical specifications

AR26/6/042 cs

MOTOR	Metric
Motor type	asynchronous motor
MECHANICAL - OUTPUT DETAILS	Metric
Vibrations	6.000 1/min
Centrifugal force	2,170 kN
Vibrations (Hz)	100,0 Hz
Centrifugal force max.	3,470 kN
ELECTRICAL - OUTPUT DETAILS	Metric
Nominal current	8,00 A
Phase	3 ~
Nominal voltage	42 V
Nominal frequency	200 Hz
Nominal power [P]	0,30 kW
ELECTRICAL SYSTEM	Metric
Cable definition	H07BQ-F 3x1,5
Operating indicator	yes
Adjusting frequency	No
Integrated transformer	No
Kind of plug	CEE-Plug 3P 32A 42V 4H
Length Cable	10,00 m
Cable cross-section	1,5 mm²
Breaker Switch On/Off	Yes

MECHANICAL DETAILS

Metric

Hole pattern length	90 mm
Length	223 mm
Height	102 mm
Hole pattern hole diameter	12 mm
Unbalanced mass/side pos2	0
Unbalanced mass/side pos1	5
Width	190 mm
Weight	6,35 kg
Hole pattern width	125 mm

ENVIRONMENT DATA

Metric

Operating temperature range	-10 - 50 °C
Sound level LpA (Standard)	EN 12649
Protection class	III / Safety extra-low voltage
Temperature of body surface	80 °C
Storage temperature range	-30 - 70 °C
Sound level LpA	70,0 dB(A)
Degree of protection	IP67

Custom Attributes

Metric

Model serie	AR26
-------------	------

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.