



**WACKER
NEUSON**
all it takes!

IREN38/042/10GV

5100054150

[Home](#) >> [Catalog](#) >> [Products](#) >> [Concrete Technology](#) >> [Internal Vibrators](#) >> [High Frequency Internal Vibrators](#) >> **IREN38/042/10GV**

IREN38/042/10GV

Material number 5100054150

Electric high frequency internal vibrator for reliable performance in concrete consolidation. Protection hose length 10 m, rubber cap.



Product details

- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

Comes with

- Internal vibrator
- Operator's manual
- General safety instructions

Technical specifications

IREN38/042/10GV

OPERATING FLUIDS

Metric

Oil volume

0,008 l

Oil specification

Klüberoil 4UH1-46N

MOTOR

Metric

Motor type

asynchronous motor

MECHANICAL - OUTPUT DETAILS

Metric

Vibrations

12.000 1/min

Vibrations (Hz)

200,0 Hz

Amplitude at air

1,90 mm

ELECTRICAL - OUTPUT DETAILS

Metric

Nominal current

7,00 A

Phase

3 ~

Nominal voltage

42 V

Nominal frequency

200 Hz

Nominal power [P]

0,41 kW

ELECTRICAL SYSTEM

Metric

Integrated transformer

No

Kind of plug

CEE-Plug 3P 32A 42V 4H

Length Cable

15,00 m

Breaker Switch On/Off

Yes

ENVIRONMENT DATA	Metric
Operating temperature range	-10 - 40 °C
Sound level LpA (Standard)	EN 12649
Protection class	III / Safety extra-low voltage
Storage temperature range	-20 - 60 °C
HAV summation (average value)	2,5 m/s ²
Uncertainty in measurement HAV	0,5 m/s ²
HAV summation (Standard)	EN ISO 20643
Sound level LpA	79,0 dB(A)
Degree of protection	IP67
Measuring method LpA	LPA1m

MECHANICAL DETAILS	Metric
Rubber cap	yes
Head diameter/-diagonal	38 mm
Length Head	345 mm
External diameter hose	31 mm
Length Hose	10,00 m
Head design	round
Weight	15,00 kg

THERMAL - OUTPUT DETAILS	Metric
Overheat limit activation	150 °C

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.