



**WACKER
NEUSON**
all it takes!

DF16

5000610299

[Home](#) >> [Catalog](#) >> [Products](#) >> [Concrete Technology](#) >> [Rebar Tier](#) >> **DF16**

DF16

Material number 5000610299

Mechanical rebar tying device. The user-friendly alternative to pliers and all electric tying devices.



Product details

Highlights

- Twisting with straight movement
- 1000 knots per hour
- Long handle

Comes with

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

- Rebar tier
- Copper grease tube
- Operator's manual

Technical specifications

DF16

OPERATING FLUIDS	Metric
Oil specification	WD-40 (nonresinous, acid-free)
Lubricant	Molykote CU-7439 plus
MECHANICAL - OUTPUT DETAILS	Metric
Bonding diameter max.	16 - 32 mm
MECHANICAL DETAILS	Metric
Length	656 mm
Height	118 mm
Width	164 mm
Weight	2,20 kg
Size of repository	77
ENVIRONMENT DATA	Metric
Storage temperature range	-25 - 50 °C

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE